



Chasen

Designed by Patricia Urquiola, 2007



Halogen - 120W

Suspension lamp providing diffused lighting. Chemically photo-etched stainless steel body and borosilicate diffuser. Liquid paint protection. Die-cast aluminum base, 30% fiberglass-reinforced polyamide ceiling rose attached to a pressed and galvanized steel ceiling fixture. In this version the light emission can be adjusted by means of a mechanical movement that opens the louvers, thereby varying the shape of the luminaire. Steel suspension cable, FEP/PVC power cord of the same color as the luminaire.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607001585
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	Halogen
Lamp holders	E27
Ilcos	IPAR
Number of heads	1
Power (W)	120

Physical

Colour	White
Length (mm)	485
Cord length (mm)	2700
Net weight (kg)	7.6
Package height (mm)	940
Package width (mm)	595
Package length (mm)	595
Package volume (m3)	0.32
IP internal	20





















Schematic light drawing



Beam Angle:		48°
h(m)	E(lx)	D(m)
1	683	0.90
2	171	1.79
3	76	2.69
4	43	3.58
5	27	4.48

Luminous flux luminaire 1300 lm

Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric

Electrical

Insulation class	I	
Frequency (Hz)	50/60	
Main voltage (Vac)	220-250	
LED voltage Vf (Vdc)	null	
Dimmable	Yes	
Dimming interface	Remote Dimmable (Dimmer Not Included)	
Batteries inside	No	





NOT INCLUDED

RF34147

LED Lamp E27 17W PAR38 Non-Dimmable INCLUDED

RF34149

LED Lamp E27 15W 3000K PAR38 Non Dimmable

Spare Parts



01. White rose assembly

RA3690209

02. White diffuser assembly

RF1636009

DOWNLOAD





RA3690209

RF1636009

White rose assembly

White diffuser assembly





F1636030 Black

Chasen

Designed by Patricia Urquiola, 2007



Halogen - 120W

Suspension lamp providing diffused lighting. Chemically photo-etched stainless steel body and borosilicate diffuser. Liquid paint protection. Die-cast aluminum base, 30% fiberglass-reinforced polyamide ceiling rose attached to a pressed and galvanized steel ceiling fixture. In this version the light emission can be adjusted by means of a mechanical movement that opens the louvers, thereby varying the shape of the luminaire. Steel suspension cable, FEP/PVC power cord of the same color as the luminaire.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607001592
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	Halogen
Lamp holders	E27
Ilcos	IPAR
Number of heads	1
Power (W)	120

Physical

Colour	Black
Length (mm)	485
Cord length (mm)	2700
Net weight (kg)	7.6
Package height (mm)	940
Package width (mm)	595
Package length (mm)	595
Package volume (m3)	0.32
IP internal	20



















Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	683	0.90
2	171	1.79
3	76	2.69
4	43	3.58
5	27	4.48

Luminous flux luminaire 1300 lm

Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric

Electrical

Insulation class	I	
Frequency (Hz)	50/60	
Main voltage (Vac)	220-250	
LED voltage Vf (Vdc)	null	
Dimmable	Yes	
Dimming interface	Remote Dimmable (Dimmer Not Included)	
Batteries inside	No	





NOT INCLUDED

RF34147

LED Lamp E27 17W PAR38 Non-Dimmable INCLUDED

RF34149

LED Lamp E27 15W 3000K PAR38 Non Dimmable

Spare Parts



01. Black rose assembly

RA3690230

02. Black diffuser assembly

RF1636030

DOWNLOAD





RA3690230

RF1636030

Black rose assembly

Black diffuser assembly