

FLOS

F3780042 Lilac

Mayday

Designed by Konstantin Grcic, 2000




Halogen - 60W

Multipurpose lighting appliance. Hook/handle, which also works as a cable winder, and an injection-moulded opaline conical diffuser made from sustainable polypropylene produced from industrial process waste. Button switch located on the handle. As no glue is used in the assembly process, Mayday is easy to dismantle so that every part can be properly recycled.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607052211
Mounting	Hand lamp
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	Halogen
Lamp holders	E27
Ilcos	HSGSA
Number of heads	1
Power (W)	60

Physical

Colour	Lilac
Length (mm)	220
Cord length (mm)	4850
Net weight (kg)	0.75
Package height (mm)	550
Package width (mm)	225
Package length (mm)	225
Package volume (m3)	0.03
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Asymmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
LED voltage Vf (Vdc)	null
Dimmable	Yes
Dimming interface	Switch Integrated (Remote Dimmable)
Plug type	Type C
Batteries inside	No

Bulbs



NOT INCLUDED

RF32563

LED Lamp 11.5W E27 220-240V
2700K A70



NOT INCLUDED

RF32564

LED Lamp 11.5W E27 220-240V
3000K A70

FLOS

F038AABA0ZZ Mustard Yellow

Mayday Outdoor

Designed by Konstantin Grcic, 2000



Socket for E14 bulb, light source not included. 220-240 V ON/OFF electric power supply. IP65 switch on the handle of the luminaire. It has a 6 meter long cable for outdoor use and an IP44 Schuko plug.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Hand lamp
Environments	Outdoor wet location
Lamp category	LED retrofit
Lamp holders	E14
Number of heads	1
Power (W)	max 10

Physical

Colour	Mustard Yellow
Orientation	Fixed
Net weight (kg)	0.9
IP internal	65



Download

[Mounting instructions](#) ZIP

Photometric Files


[LDT / IES](#) ZIP

[LDT / IES](#) ZIP


Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



Schematic light drawing



Photometric

Lighting type Direct


Electrical

Insulation class	II
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Dimmable	No
Emergency type	No

Notes

Bulb not included. LED: max 10W - E14


Bulbs



NOT INCLUDED

RF32291

LED Lamp E14 8W 3000K T28



NOT INCLUDED

RF32290

LED Lamp E14 8W 2700K T28