



Outdoor



4695
Ø 20 x 12 cm



4697
Ø 15 x 9 cm




4700
Ø 20 x 12 cm



4702
Ø 15 x 9 cm

4695



- Finishes**
- **22/** _ _ Graphite Black (NCS S 8000-N)
 - **25/** _ _ Beige D1 (NCS S 4005-Y50R)
 - **53/** _ _ Green M1 (NCS S 6005-G80Y)

LED Colour Temperature
/1_ 2700 K - 750,2 lm
F >90

Control

4695 _ _ / _ _
_ _ / _ **0** On/ Off
_ _ / _ **1 30** DALI-2 (Remote)
_ _ / _ **Z 30** Casambi (Remote)

Materials

Body: Aluminum.
Diffuser: PC- Polycarbonate.


Light Source and electronics
1 x LED STRIP 7,8W 350 mA
Constant Current 350 mA
100~277V 50/60Hz

Packaging

1 Box 0,30 x 0,27 x 0,18 m
Vol 0,0146 m³
Gross weight 3,4 Kg Net weight 2,7 Kg

LED IP65 CE UK ENE Multi-volt

4697



- Finishes**
- **22/** _ _ Graphite Black (NCS S 8000-N)
 - **25/** _ _ Beige D1 (NCS S 4005-Y50R)
 - **53/** _ _ Green M1 (NCS S 6005-G80Y)

LED Colour Temperature
/1_ 2700 K - 375,9 lm
F >90

Control

4697 _ _ / _ _
_ _ / _ **0** On/ Off
_ _ / _ **1 30** DALI-2 (Remote)
_ _ / _ **Z 30** Casambi (Remote)

Materials


Body: Aluminum.
Diffuser: PC- Polycarbonate.

Light Source and electronics
1 x LED STRIP 4,6W 350 mA
Constant Current 350 mA
100~240V 50/60Hz

Packaging

1 Box 0,24 x 0,20 x 0,13 m
Vol 0,0624 m³
Gross weight 1,9 Kg Net weight 1,5 Kg

LED IP65 CE UK ENE Multi-volt

4700 	Finishes ● 22/ _ _ Graphite Black (NCS S 8000-N) ● 25/ _ _ Beige D1 (NCS S 4005-Y50R) ● 53/ _ _ Green M1 (NCS S 6005-G80Y)
--	---

