

FLOS

 F9520039 Green


Wireline

Designed by Formafantasma, 2019

45W - 2793lm - 2700K - CRI> 90



Suspension lamp with diffused light. Tubular in transparent extruded glass and internal diffuser in opal PC. Ferrules made with CNC technology in satin stainless steel. Extruded cable in pink and forest green rubber. Injection molded PC rosette in the same finishes as the cable. The electronics integrated in the ceiling rose allows the use of different dimerization systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the luminous flux can be set during installation, with the push system included in the canopy. Useful length of the cable 3mt.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	45
System power (W)	45
System flux (lm)	2793

Physical

Colour	Green
Length (mm)	1300
Cord length (mm)	4050
Net weight (kg)	7.8
Package height (mm)	0
Package width (mm)	0
Package length (mm)	0
Package volume (m3)	0.05
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ LDT](#)


Technical Drawings

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
LED voltage Vf (Vdc)	null
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F




Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional

Spare Parts



00.	Power supply unit for led	RF22934
00.	12-48V Led Dimmer	RF26994
10.	WireLine Body	F9521000
20.	WireLine Green Wire	F9522039
30.	Assembly Suspension Rose for Wirelines Green	RF30045
40.	Assembly Rose Cover Green	RF9523139



RF22934
Power supply unit for led



RF26994
12-48V Led Dimmer



F9521000
WireLine Body



F9522039
WireLine Green Wire



RF30045
Assembly Suspension Rose for
Wirelines Green



RF9523139
Assembly Rose Cover Green