

FLOS

SA.5006.1F Raw

Soft Spun LED Small

Designed by Sebastian Wrong, 2010




LED - Top LED - 28W - 1184lm - 3000K - CRI> 90

Recessed luminaire for LED lamp. Non-dimmable 220/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Recessed
Environments	Indoor dry location
Light Source Type	LED
LED type	Top LED
Lamp category	LED
Iicos	LED
Number of heads	1
Power (W)	28
System power (W)	35
System flux (lm)	1184

Physical

Colour	Raw
Trim	No
Orientation	Fixed
Recessed depth (mm)	35
Length (mm)	590
Net weight (kg)	11
IP internal	20
IP external	20

Download

Mounting instructions

[↓ PDF](#)

Ecodesign and Energy Labelling



Non-replaceable light source

	IP 20	IK 00	IP 20
--	----------	----------	----------

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	240
Alternating current voltage (Vac)	240
Driver	Remote included
Dimmable	No
Dimming type	Non Dimmable
Dimming interface	Not Dimmable
Emergency type	No

FLOS

SA.5007.1F Raw

Soft Spun LED Large


Designed by Sebastian Wrong



Recessed luminaire for LED lamp. Non-dimmable 220/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Wall recessed
Environments	Indoor dry location
Lamp category	LED
Icos	No
Power (W)	35 + 1.4
Source flux (lm)	1880
System flux (lm)	1391

Physical

Colour	Raw
Trim	No
Orientation	Fixed
Net weight (kg)	28
IP internal	20
IP external	20

Download

[Mounting instructions](#)

[↓ PDF](#)

UK CA	IP	IP
	20	20

Photometric

Lighting type	Indirect
Light distribution	Symmetric
CCT (K)	3000
CRI>	90

Electrical

Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Notes

LED White diffuser / LED White base
